
RbFly Library

Release 0.8.3

Artur Wroblewski

May 04, 2024

RbFly Library

I	RbFly Library	3
1	Overview	4
1.1	Features	4
1.2	Requirements	4
1.3	Installation	4
1.4	Documentation	4
1.5	Links	5
1.6	Acknowledgements	5
2	License	5
3	Quick Start	5
4	Publish Messages	6
4.1	Send Single Message	7
4.2	Send Batch of Messages	7
4.3	Fast Batch Publishing	7
4.4	Publishing Exceptions	8
5	Read Messages	8
5.1	Subscribe to a Stream	8
5.2	Message Context	8
5.3	Offset Specification	8
5.4	Offset Reference	9
6	Manage Connection	10
7	Deduplicate Messages	11
7.1	Publish Messages with Id	11
7.2	Order of Messages	12
8	Manage Streams	12
8.1	RabbitMQ CLI Tools	12
8.2	Automation Tools	13
8.3	RbFly API	13
II	RbFly Library Reference	14

9 RabbitMQ Streams API	15
9.1 Broker Connection API	15
9.2 Publisher and Subscriber API	16
9.3 Data Types	20
9.4 Deprecated API	20
10 Connection URI	20
11 Message Data Types	21
12 Changelog	22
12.1 Year 2024	22
12.2 Year 2023	22
12.3 Year 2022	24
Index	27

Part I

RbFly Library

1 Overview

RbFly is a library for RabbitMQ Streams using Python asyncio.

1.1 Features

The library is designed and implemented with the following qualities in mind

1. Simple, flexible, and asynchronous Pythonic API with type annotations.
2. Use of AMQP 1.0 message format to enable interoperability between RabbitMQ Streams clients.
3. Performance. For example, RbFly can be over 3.5 times faster than other, similar solutions when publishing messages to a streaming broker ([Section 1.4](#) references appropriate report).
4. Auto reconnection to RabbitMQ broker with lazily created connection objects.

RbFly supports many RabbitMQ Streams broker features

1. Publishing single messages, or in batches, with confirmation.
2. Subscribing to a stream at a specific point in time, from a specific offset, or using offset reference.
3. Writing stream offset reference.
4. Message deduplication.
5. Integration with AMQP 1.0 ecosystem at message format level.

1.2 Requirements

RbFly requires

- Python 3.10, or later
- RabbitMQ 3.11.17, or later
- Cython 3.0.0 (for development)

1.3 Installation

Install or upgrade RbFly from PyPi with pip command:

```
$ pip install -U rbfly
```

1.4 Documentation

The documentation of RbFly library is hosted at project's website at the address

<https://wrobell.dcmmod.org/rbfly/>

The documentation consists of multiple parts. Each part can be downloaded in PDF format

Document	URL
RbFly Library	https://wrobell.dcmmod.org/rbfly/rbfly-0.8.3.pdf
RbFly Library Performance Report	https://wrobell.dcmmod.org/rbfly/rbfly-performance-0.8.3.pdf

1.5 Links

1. RbFly project website: <https://wrobell.dcmo.org/rbfly/index.html>
2. Report bugs for RbFly project: <https://gitlab.com/wrobell/rbfly/-/issues>
3. View RbFly library source code: <https://gitlab.com/wrobell/rbfly>
4. RabbitMQ Streams: <https://www.rabbitmq.com/streams.html>
5. RabbitMQ Streams Java library: <https://rabbitmq.github.io/rabbitmq-stream-java-client/stable/htmlsingle/>
6. RabbitMQ discussions: <https://groups.google.com/g/rabbitmq-users/>

1.6 Acknowledgements

The design and implementation of RbFly library is inspired by other projects

- [asyncpg](#)
- [rstream](#)
- [aioredis](#)
- [aiokafka](#)

2 License

RbFly library is licensed under terms of [GPL license, version 3](#). As stated in the license, there is no warranty, so any usage is on your own risk.

3 Quick Start

The example below demonstrates various RbFly library features, which can be utilized in an application using RabbitMQ Streams:

- creating RabbitMQ Streams client using connection URI
- creating a stream (*demo* coroutine)
- creating a stream publisher and publishing messages to a stream (*send_data* coroutine)
- subscribing to a stream and receiving messages from a stream (*receive_data* coroutine)
- the script continues to run if RabbitMQ Streams broker stops and starts again

```
import asyncio
from datetime import datetime

import rbfly.streams as rbs

STREAM = 'rbfly-demo-stream' # stream to send message to

async def send_data(client: rbs.StreamsClient) -> None:
    # create publisher and send messages to the stream in a loop
    async with client.publisher(STREAM) as publisher:
        while True:
            await publisher.send('hello')

            print('{} message sent'.format(datetime.now()))
```

(continues on next page)

```

        await asyncio.sleep(5)

    async def receive_data(client: rbs.StreamsClient) -> None:
        # subscribe to the stream and receive the messages
        async for msg in client.subscribe(STREAM):
            print('{} got: {}'.format(datetime.now(), msg))
            print()

    @rbs.connection # close connection to RabbitMQ Streams broker at exit
    async def demo(client: rbs.StreamsClient) -> None:
        # create stream; operation does nothing if a stream exists; stream can
        # be created by an external tool;
        # this is first operation to RabbitMQ Streams broker in this demo,
        # so a connection is created by RbFly
        await client.create_stream(STREAM)

        await asyncio.gather(send_data(client), receive_data(client))

    # create RabbitMQ Streams client
    client = rbs.streams_client('rabbitmq-stream://guest:guest@localhost')

    asyncio.run(demo(client))

```

The source code of the demo can be downloaded from [RbFly code repository](#).

The following sections of the documentation discuss the features of RbFly library in more detail.

4 Publish Messages

To send messages to a RabbitMQ stream create a RabbitMQ Streams publisher with `publisher()` method of `StreamsClient()` class. There are multiple types of publishers implemented by the following classes

`rbfly.streams.Publisher`

Send a message and wait for RabbitMQ Streams broker to confirm that the message is received. Multiple asynchronous coroutines can send messages with the same publisher concurrently. This is the slowest way of sending messages. It is the default RbFly publisher.

`rbfly.streams.PublisherBatchLimit`

Batch multiple messages, then send them to a stream with the flush method. Batch method blocks when a limit of messages is reached, so an application does not run out of memory. Batching and flushing can be performed concurrently from different asynchronous coroutines. This is faster method of sending messages, than the previous one.

`rbfly.streams.PublisherBatchFast`

Batch multiple messages, then send them to a stream with the flush method. The number of messages in a batch is limited by a maximum length of Python list. An application needs to flush messages on a regular basis to sustain its performance, and to avoid running out of memory. Use it only when messages can be batched and flushed in a sequence, i.e. from the same asynchronous coroutine. This is the fastest method of sending messages to a stream, but provides no coordination between batch and flush methods.

Note: RabbitMQ Streams publisher uses publisher reference name for message deduplication. By default, a publisher name is set using `<hostname>/<pid>` format.

If the naming scheme is not sufficient, then publisher reference name should be overridden when creating a publisher.

4.1 Send Single Message

To send messages one by one, create a RabbitMQ Streams publisher and send messages with `send()` asynchronous coroutine:

```
async with client.publisher('stream-name') as publisher:
    message = 'hello'
    await publisher.send(message)
```

The coroutine sends a message and waits for RabbitMQ Streams broker for the published message confirmation.

4.2 Send Batch of Messages

If an application has to send a batch of messages from multiple asynchronous coroutines, then use publisher implemented by `PublisherBatchLimit` class.

Enqueue a message with `batch()` asynchronous coroutine method. The method blocks if an applications reaches limit of number of messages. To unblock, use `flush()` asynchronous coroutine method:

```
async def run_app(client: StreamsClient) -> None:
    # note: publisher is flushed on exit of the context manager as well
    async with client.publisher('stream-name', cls=PublisherBatchLimit) as publisher:
        await asyncio.gather(batch(publisher), flush(publisher))

async def batch(publisher: PublisherBatchLimit) -> None:
    await publisher.batch('hello 1')
    await publisher.batch('hello 2')

async def flush(publisher: PublisherBatchLimit) -> None:
    while True:
        asyncio.sleep(0.2) # flush messages 5 times per second
        await publisher.flush()
```

Use `flush()` asynchronous coroutine to send messages to RabbitMQ Streams broker and wait for confirmation of receiving the messages.

4.3 Fast Batch Publishing

To send messages in batch mode create publisher using `PublisherBatchFast` class. Enqueue each message with `batch()` method:

```
async with client.publisher('stream-name', cls=PublisherBatchFast) as publisher:
    publisher.batch('hello 1')
    publisher.batch('hello 2')
    await publisher.flush()
```

Use `flush()` asynchronous coroutine to send the messages to RabbitMQ Streams broker and wait for confirmation of receiving the messages.

4.4 Publishing Exceptions

RbFly might raise the following exceptions when publishing messages

TypeError

A message or part of a message is of a type not recognized by RbFly's AMQP format encoder.

ValueError

A message has invalid value. For example, a message does not fit within the frame of RabbitMQ Streams protocol, or a string exceeds maximum allowed length ($2^{32} - 1$).

5 Read Messages

5.1 Subscribe to a Stream

To read messages from RabbitMQ Streams broker, subscribe to a RabbitMQ stream with `subscribe()` method of `StreamsClient` class. The method is an asynchronous iterator, which yields stream messages:

```
async for msg in client.subscribe('stream-name'):
    print(msg)
```

The method accepts the offset parameter. This is described in more detail in [Section 5.3](#).

5.2 Message Context

A RabbitMQ Streams message has a set of properties like offset or timestamp. Also, AMQP 1.0 message, beside message body, can have additional data attached like header or application properties.

The additional information is available via `MessageCtx` object, which can be retrieved with `get_message_ctx()` function, for example:

```
async for msg in client.subscribe('stream-name'):
    print(get_message_ctx().stream_offset)
```

5.3 Offset Specification

RabbitMQ Streams offset specification is used by a client application to declare, which messages from a streams should be received on stream subscription.

The `subscribe()` method accepts optional `offset` parameter, which can be one of the following:

`rbfly.streams.Offset.NEXT`

Receive new messages from a stream only. Default offset specification.

`rbfly.streams.Offset.FIRST`

Receive all messages, starting with the very first message in a stream. Equivalent to `Offset.offset(0)`.

`rbfly.streams.Offset.LAST`

Receive messages from a streams starting with first message stored in the current stream chunk (see also below).

`rbfly.streams.Offset.offset()`

Receive messages from a stream starting with specific offset value.


`rbfly.streams.Offset.reference()`

Use the reference to get the offset stored in a stream. Receive messages starting from the next offset (this is `offset + 1`).

`rbfly.streams.Offset.timestamp()`

Receive messages from a stream starting with the specified timestamp of a message.

The following diagram visualizes offset location in a stream when each chunk has 100 messages:



Note: Timestamp is Erlang runtime system time. It is a view of POSIX time.

5.4 Offset Reference

RabbitMQ Streams supports storing an offset value in a stream using a string reference, and receiving an offset value using the reference.

Use *offset reference specification* to read messages from a stream starting after stored offset value:

```
messages = client.subscribe('stream-name', offset=Offset.reference('stream-ref'))
try:
    async for msg in messages:
        print msg
finally:
    await client.write_offset('stream-name', 'stream-ref')
```

In the example above, RbFly library performs the following actions

- read offset value, stored for offset reference string *stream-ref*, from RabbitMQ Streams broker
- start reading messages of stream *stream-name* with the offset value increased by one (start reading *after* stored value)
- keep offset value of last received message in memory

The example saves offset value with `write_offset()` method. By default, the method saves offset value of last stream message. Custom offset value, can also be specified, see *the method documentation* for details.

Note: How and when offset value shall be saved is application dependant.

6 Manage Connection

Use `streams_client()` function to declare connection to RabbitMQ Streams broker. The function creates RabbitMQ Streams client object, which is used to *create streams*, *publish messages* to a stream, and *subscribe* to a stream.

Whenever an action of an application requires an interaction with RabbitMQ Streams broker, a connection is created, or existing connection is reused.

When a broker is restarted (i.e. after upgrade, or after crash), then RbFly reconnects the client, and retries an interrupted action.




Figure 6.1: RbFly reconnecting an application to RabbitMQ Streams broker in action

Screenshot of Grafana plot of stream messages received by RabbitMQ Streams broker from an application. There are two restarts of RabbitMQ service to update the broker. Each time, RbFly receives disconnection request from the broker, caches messages of an application, and flushes messages to the broker when a new connection is established. No data is lost in the process.

Properly closing a connection to RabbitMQ Streams broker requires use of `connection()` decorator. Use it to decorate a Python asynchronous coroutine function. The decorator closes a connection to a broker when the decorated coroutine exits.

The example below is a skeleton of a Python program creating RabbitMQ Streams broker client, implementing asynchronous coroutine to interact with the broker, and to close connection on the coroutine exit:

```
import asyncio
import rbfly.streams as rbs

@rbs.connection
async def streams_app(client: rbs.StreamsClient) -> None:
    ...
    # interaction with RabbitMQ Streams broker
    ...

client = rbs.streams_client('rabbitmq-stream://guest:guest@localhost')
asyncio.run(streams_app(client))
```

7 Deduplicate Messages

RabbitMQ Streams allows applications to publish messages to a stream with message deduplication.

RbFly generates message publishing ids by default. It also supports message deduplication, but it is responsibility of an application to

- assign reference name to a publisher of messages
- assign a publishing id to a message in an unique fashion
- ensure publishing ids of messages are strictly increasing
- keep track of publishing id of a message between application restarts

Note: A RbFly publisher object remembers publishing id of a last message. Therefore, it is possible to switch between providing a message publishing id by an application, and generating message publishing id by RbFly library.

However, it is not recommended for an application to change the approach to message publishing ids during application lifetime.

7.1 Publish Messages with Id

To enable deduplication of messages create a publisher with an unique reference name for given application. Create context for each message with `stream_message_ctx()` function, and publish message context with a publisher.

The following example publishes *10* messages every second. Every time, the messages are assigned the same message publishing id. The number of messages in the stream is always *10*, even when the script is restarted.

```
import asyncio
from datetime import datetime

import rbfly.streams as rbs

STREAM = 'rbfly-demo-dedup-stream'

# an application uses an unique publisher name; it allows message
# deduplication between application restarts
PUBLISHER = 'demo-publisher'

async def send_data(client: rbs.StreamsClient) -> None:
    async with client.publisher(STREAM, name=PUBLISHER) as publisher:
        while True:
            for i in range(10):
                # use `stream_message_ctx` function to create message
                # context and assign publishing id
                ctx = rbs.stream_message_ctx('hello', publish_id=i)
                await publisher.send(ctx)

            print('{} messages sent'.format(datetime.now()))
            await asyncio.sleep(1)

@rbs.connection
async def demo(client: rbs.StreamsClient) -> None:
    await client.create_stream(STREAM)
    await send_data(client)
```

(continues on next page)

(continued from previous page)

```
client = rbs.streams_client('rabbitmq-stream://guest:guest@localhost')
asyncio.run(demo(client))
```

Note: Observe number of messages in a RabbitMQ stream with `rabbitmqctl list_queues` command, or in the management web console.

When an application is restarted, and a publisher is created with its reference name, then RbFly library queries RabbitMQ Streams broker to get the last message publishing id. A RbFly's publisher object provides its last message publishing id via `message_id` attribute.

7.2 Order of Messages

It is an application's responsibility to publish messages with their publishing id strictly increasing. Providing out-of-order message publishing ids has an undefined result.

When publishing a single message at a time (see [Section 4.1](#)), then publishing id, of each new message, has to have greater value comparing to a previous one. When existing messages are sent to a broker, then the order does not matter - messages are ignored due to RabbitMQ Stream's deduplication feature.

For new messages, the same rule as above applies to a batch publisher. However, when republishing messages, then messages within a batch have to be sorted by their publishing id.

The batch publisher with a batch limit (see [Section 4.2](#)) enables an application to batch messages from multiple asynchronous coroutines. Therefore, messages and their publishing ids can be enqueued out-of-order. The publisher sorts messages by their publishing id when sending messages to RabbitMQ Streams broker with `flush()` method.

The fast batch publisher (see [Section 4.3](#)) does not control the order of message publishing ids. An application takes the responsibility to provide them in a strictly increasing order.

8 Manage Streams

There are multiple ways to manage RabbitMQ streams. The recommended way to create or delete a RabbitMQ stream is to use RabbitMQ CLI tools or infrastructure automation software.

8.1 RabbitMQ CLI Tools

Use `rabbitmqadmin` and `rabbitmqctl` command-line RabbitMQ tools to create and delete streams.

To create a RabbitMQ stream, declare a queue with `queue_type` argument set to `stream`:

```
$ rabbitmqadmin declare queue name=yellow.carrot queue_type=stream \
  arguments='{"x-max-age": "24h"}'
```

To delete a stream use `rabbitmqctl` command-line tool:

```
$ rabbitmqctl delete_queue yellow.carrot
```

8.2 Automation Tools

RabbitMQ streams can be created using automation tools like [Terraform](#) or [Ansible](#)

- [Ansible RabbitMQ Queue Module](#)
- [Terraform RabbitMQ Queue Resource](#)

As with RabbitMQ CLI tools, declare a RabbitMQ queue, and use *x-queue-type* argument set to *stream*. For example, for Ansible:

```
- name: Create a RabbitMQ stream
become: yes
community.rabbitmq.rabbitmq_queue:
  name: yellow.carrot
  arguments:
    x-queue-type: stream
    x-max-age: 1D
```

8.3 RbFly API

Note: This method of creating and deleting RabbitMQ streams is not recommended. It is used for testing and in short examples only.

RbFly allows to create and delete streams programmatically with `create_stream()` and `delete_stream()` methods:

```
await client.create_stream('yellow.carrot')
await client.delete_stream('yellow.carrot')
```

Part II

RbFly Library Reference

9 RabbitMQ Streams API

9.1 Broker Connection API

<code>rbfly.streams.streams_client</code>	Create RabbitMQ Streams client using connection URI.
<code>rbfly.streams.connection</code>	Decorator to manage RabbitMQ Streams client connection.
<code>rbfly.streams.StreamsClient</code>	RabbitMQ Streams client.

`rbfly.streams.streams_client(uri: str, /, ssl: SSLContext | None = None) → StreamsClient`
Create RabbitMQ Streams client using connection URI.

Parameters

- **uri** – Connection URI.
- **ssl** – TLS/SSL context object.

`rbfly.streams.connection(coro: Callable[[Concatenate[Trc, P]], Coroutine[Any, Any, T]]) → Callable[[Concatenate[Trc, P]], Coroutine[Any, Any, T]]`

`rbfly.streams.connection(coro: Callable[[Concatenate[Trc, P]], AsyncIterator[T]]) → Callable[[Concatenate[Trc, P]], AsyncIterator[T]]`

Decorator to manage RabbitMQ Streams client connection.

Streams client implements connection manager abstract class.

Streams client has to be the first parameter of coroutine `coro`.

Streams client is disconnected on exit of the coroutine using connection manager API.

Parameters

coro – Coroutine using RabbitMQ Streams client.

class `rbfly.streams.StreamsClient(connection_info: ConnectionInfo)`

RabbitMQ Streams client.

async `create_stream(stream: str) → None`

Create RabbitMQ stream.

Method ignores error received from RabbitMQ Streams broker if the stream exists.

Parameters

stream – RabbitMQ stream name.

async `delete_stream(stream: str) → None`

Delete RabbitMQ stream.

Method ignores error received from RabbitMQ Streams broker if the stream does not exist.

Parameters

stream – RabbitMQ stream name.

publisher `(stream: str, *, name: str | None = None) → tp.AsyncContextManager[Publisher]`

publisher `(stream: str, *, name: str | None = None, cls: type[T]) → tp.AsyncContextManager[T]`

Create publisher for RabbitMQ stream.

The single message, AMQP publisher is used by default.

The stream must exist.

Publisher reference name is used for deduplication of messages. By default, the publisher name is `<hostname>/<pid>`. Override it, if this scheme does not work for a specific application, i.e. when using threads.

Parameters

- **stream** – RabbitMQ stream name.
- **name** – RabbitMQ stream publisher reference name.
- **cls** – Publisher class.

See also:

- `rbfly.streams.Publisher`
- `rbfly.streams.PublisherBatchFast`
- `rbfly.streams.PublisherBatchLimit`

async subscribe(*stream: str, *, offset: Offset = Offset.NEXT, timeout: float = 0, amqp: bool = True*)
→ `AsyncIterator[rbfly.streams.types.AMQPBody]`

Subscribe to the stream and iterate over messages.

Parameters

- **stream** – Name of RabbitMQ stream to subscribe to.
- **offset** – RabbitMQ Streams offset specification.
- **timeout** – Raise timeout error if no message received within specified time (in seconds).
- **amqp** – Messages are in AMQP 1.0 format if true. Otherwise no AMQP decoding.

async write_offset(*stream: str, reference: str, value: int | None = None*) → `None`

Write RabbitMQ stream offset value using the reference string.

When offset value is not specified, then the last message context is retrieved and its stream offset value is stored. If there is no last message context to retrieve, then method does nothing.

Parameters

- **stream** – Name of RabbitMQ stream.
- **reference** – Offset reference string.
- **value** – Offset value to be stored.

9.2 Publisher and Subscriber API

<code>rbfly.streams.stream_message_ctx</code>	Create message context for RabbitMQ Streams publisher.
<code>rbfly.streams.get_message_ctx</code>	Get current context of AMQP message.
<code>rbfly.streams.StreamsClient</code>	RabbitMQ Streams client.
<code>rbfly.streams.Publisher</code>	RabbitMQ Streams publisher for sending a single message.
<code>rbfly.streams.PublisherBatchLimit</code>	RabbitMQ Streams publisher for sending limited batch of messages.
<code>rbfly.streams.PublisherBatchFast</code>	RabbitMQ Streams publisher for sending a batch of messages.
<code>rbfly.streams.MessageCtx</code>	AMQP message context.
<code>rbfly.streams.Offset</code>	Offset specification for RabbitMQ stream subscription.

`rbfly.streams.stream_message_ctx`(*body: AMQPBody*, *, *publish_id: int | None = None*, *app_properties: AMQPAppProperties = {}*) → *MessageCtx*

Create message context for RabbitMQ Streams publisher.

Message publish id is optional - a publisher assigns one if not specified. Message publish id can be used for message deduplication. If an application provides message publish ids, then it is its responsibility to track them and keep the ids strictly increasing.

Application properties are part of AMQP message. The properties can be used for filtering or routing.

Parameters

- **body** – Message data to be sent to a stream.
- **publish_id** – Message publish id.
- **app_properties** – Application properties, part of AMQP message.

`rbfly.streams.get_message_ctx`() → *MessageCtx*

Get current context of AMQP message.

class `rbfly.streams.Publisher`

RabbitMQ Streams publisher for sending a single message.

See also:

- `rbfly.streams.PublisherBatchLimit`
- `rbfly.streams.PublisherBatchFast`

name

name: unicode Publisher reference name.

stream

stream: unicode RabbitMQ stream name.

message_id

message_id: int Last value of published message id.

async `send`(*self*, *message: AMQPBody | MessageCtx*) → *None*

Send AMQP message to a RabbitMQ stream.

The asynchronous coroutine waits for message delivery confirmation from RabbitMQ Streams broker.

A *message* is simply application data of type `AMQPBody`, or message context (class `MessageCtx`).

Parameters

message – AMQP message to publish.

See also:

- `stream_message_ctx`()
- `AMQPBody`
- `MessageCtx`

class `rbfly.streams.PublisherBatchLimit`

RabbitMQ Streams publisher for sending limited batch of messages.

The publisher performs coordination between the batch and flush asynchronous coroutines to allow sending only limited number of messages.

See also:

- `rbfly.streams.PublisherBatchFast`

- `rbfly.streams.Publisher`

name

name: unicode Publisher reference name.

stream

stream: unicode RabbitMQ stream name.

message_id

message_id: int Last value of published message id.

async batch(*self*, *message*: `AMQPBody` | `MessageCtx`, *, *max_len*: `int`) → `None`

Enqueue AMQP message for batch processing with RabbitMQ Streams broker.

The asynchronous coroutine blocks when *max_len* messages are enqueued. To unblock, call `PublisherBatchLimit.flush()` method.

A *message* is simply application data of type `AMQPBody`, or message context (class `MessageCtx`).

Parameters

- **message** – AMQP message to publish.
- **max_len** – Maximum number of messages in a batch.

See also:

- `PublisherBatchLimit.flush()`
- `stream_message_ctx()`
- `AMQPBody`
- `MessageCtx`

async flush(*self*) → `None`

Flush all enqueued messages and unblock `PublisherBatchLimit.batch()` asynchronous coroutines.

See also:

`PublisherBatchLimit.batch()`

class `rbfly.streams.PublisherBatchFast`

RabbitMQ Streams publisher for sending a batch of messages.

The number of messages in a single batch is limited by the maximum length of the Python list type on a given platform.

- `rbfly.streams.PublisherBatchLimit`
- `rbfly.streams.Publisher`

name

name: unicode Publisher reference name.

stream

stream: unicode RabbitMQ stream name.

message_id

message_id: int Last value of published message id.

batch(*self*, *message*: `AMQPBody` | `MessageCtx`) → `None`

Enqueue AMQP message for batch processing with RabbitMQ Streams broker.

A *message* is simply application data of type `AMQPBody`, or message context (class `MessageCtx`).

Parameters

message – AMQP message to publish.

See also:

- *PublisherBatchFast.flush()*
- *stream_message_ctx()*
- AMQPBody
- *MessageCtx*

async flush(*self*) → *None*

Flush all enqueued messages.

class `rbfly.streams.MessageCtx`

AMQP message context.

Variables

- **body** – Message body.
- **annotations** – Message annotations.
- **app_properties** – Application properties.
- **stream_offset** – RabbitMQ stream offset value.
- **stream_timestamp** – RabbitMQ stream offset timestamp value.
- **stream_publish_id** – RabbitMQ stream message publishing id.

class `rbfly.streams.Offset`(*type: OffsetType, value: int | float | str | None = None*)

Offset specification for RabbitMQ stream subscription.

FIRST: *Offset* = *Offset.FIRST*

Receive all messages, starting with the very first message in a stream. Equivalent to *Offset.offset(0)*.

LAST: *Offset* = *Offset.LAST*

Receive messages from a streams starting with first message stored in the current stream chunk.

NEXT: *Offset* = *Offset.NEXT*

Receive new messages from a stream only. Default offset specification.

static *offset*(*offset: int*) → *Offset*

Create offset specification with offset value.

Parameters

offset – Offset value.

static *reference*(*reference: str*) → *Offset*

Create offset specification, which queries and stores stream offset with offset reference.

Parameters

reference – Offset reference string.

static *timestamp*(*timestamp: float*) → *Offset*

Create offset specification with timestamp value.

Parameters

timestamp – Unix timestamp in seconds since epoch.

9.3 Data Types

<code>rbfly.types.Symbol</code>	Symbolic value from a constrained domain as defined by AMQP 1.0.
<code>rbfly.types.AMQPScalar</code>	AMQP simple type.
<code>rbfly.types.AMQPBody</code>	Application data sent as AMQP message.
<code>rbfly.types.AMQPAppProperties</code>	Application properties sent with AMQP message.

class `rbfly.types.Symbol` (*name: str*)

Symbolic value from a constrained domain as defined by AMQP 1.0.

The class is also exported via `rbfly.streams` module.

`rbfly.types.AMQPScalar`: **TypeAlias** = `None | str | bool | int | float | datetime.datetime | uuid.UUID | rbfly.types.Symbol | bytes`

AMQP simple type.

The type is also exported via `rbfly.streams` module.

`rbfly.types.AMQPBody`: **TypeAlias** = `collections.abc.Sequence['AMQPBody'] | dict['AMQPBody', 'AMQPBody'] | None | str | bool | int | float | datetime.datetime | uuid.UUID | rbfly.types.Symbol | bytes`

Application data sent as AMQP message.

It is sent by a publisher and received by a subscriber.

The type is also exported via `rbfly.streams` module.

`rbfly.types.AMQPAppProperties`

Application properties sent with AMQP message.

The type is also exported via `rbfly.streams` module.

alias of `dict[str, None | str | bool | int | float | datetime | UUID | Symbol | bytes]`

9.4 Deprecated API

Deprecated since version 0.7.0:

class `rbfly.streams.PublisherBatch`

Use `rbfly.streams.PublisherBatchFast` class instead.

class `rbfly.streams.PublisherBatchMem`

Use `rbfly.streams.PublisherBatchLimit` class instead.

10 Connection URI

The string specifying RabbitMQ Streams connection is URI in the format:

```
rabbitmq-stream://[user[:password]@][host[:port]][/vhost]]
```

or for TLS:

```
rabbitmq-stream+tls://[user[:password]@][host[:port]][/vhost]]
```

The description of the URI parts is as follows

user

Name of an user connecting to RabbitMQ Streams broker.

password

Password of the user.

host

RabbitMQ Streams broker hostname, *localhost* by default.

port

RabbitMQ Streams broker port, *5552* by default.

vhost

Virtual host of RabbitMQ Streams broker, it is */* (slash) by default.

Examples of valid URI values:

```
rabbitmq-stream://
rabbitmq-stream://localhost
rabbitmq-stream://localhost/
rabbitmq-stream://good-rabbit:1552/carrot
rabbitmq-stream://user@good-rabbit
rabbitmq-stream://user:passta@good-rabbit/carrot
```

Examples of valid URI values for TLS connections:

```
rabbitmq-stream+tls://
rabbitmq-stream+tls://localhost
rabbitmq-stream+tls://localhost/
rabbitmq-stream+tls://good-rabbit:1551/carrot
rabbitmq-stream+tls://user@good-rabbit
rabbitmq-stream+tls://user:passta@good-rabbit/carrot
```

11 Message Data Types

Note: Support for AMQP 1.0 encoding and decoding is work in progress.

Message body, sent to a RabbitMQ stream, is any Python object having one of the types

bytes

A data section of AMQP message containing opaque binary data. It can carry any binary message encoded with third-party encoders like [MessagePack](#).

The data type is also accepted as a member of a container type like sequence, or dictionary.

None

An AMQP message with null value.

str

An AMQP message with string value encoded with Unicode.

bool

An AMQP message with boolean value (true or false).

int

An AMQP message with integer value. The value is encoded with AMQP type as defined by the table

Value Range	AMQP Type Name
$[-2^{31}, 2^{31} - 1]$	int
$[-2^{63}, 2^{63} - 1]$	long
$[2^{63}, 2^{64} - 1]$	ulong

All other, AMQP integer types are parsed as Python `int` type.

float

An AMQP message with value of AMQP type double. AMQP type float is parsed as value of Python type float, as well.

sequence

An AMQP message with value of AMQP type list. Python `list` and `tuple` types are supported when serializing to AMQP format. Always decoded into a Python list.

dict

An AMQP message with value of AMQP type map. The order of key-value pairs in a map is preserved on encoding and decoding. In AMQP standard, the order of key-value pairs is semantically important, but this is not the case for Python dictionary.

datetime.datetime

An AMQP message with value of AMQP type timestamp. Unaware datetime object is encoded as UTC timestamp value. Decoded datetime object has UTC timezone.

uuid.UUID

An AMQP message with an universally unique identifier as defined by RFC-4122, section 4.1.2.

Symbol

Symbolic value from a constrained domain. The value is an ASCII string.

12 Changelog

12.1 Year 2024

2024-05-04, ver. 0.8.3

- fix errors in `rbfly.streams.connection` decorator

2024-03-19, ver. 0.8.2

- improve type annotations for `rbfly.streams.connection` decorator

2024-01-07, ver. 0.8.1

- fix typo: `stream_messsage_ctx` -> `stream_message_ctx`

12.2 Year 2023

2023-11-02, ver. 0.8.0

- allow tls connections to rabbitmq streams broker
- publish performance test results for amqp 1.0 codecs
- flush batch publisher on exit from an asynchronous context manager of a publisher
- avoid publisher ids and subscriber ids overflow by reusing and controlling the ids

2023-09-15, ver. 0.7.3

- add support for null values in amqp messages
- use cython 3.0.2 to build rbfly binary extensions

2023-07-09, ver. 0.7.2

- fix binary only decoder of rabbitmq streams messages
- fix reading duplicate messages when re-subscribing to a rabbitmq stream

2023-06-25, ver. 0.7.1

- fix reconnection to rabbitmq streams broker, which was failing due to hidden subscriber class attributes

2023-06-21, ver. 0.7.0

- rbfly is beta software, now
- add support for deduplication of published messages
- add support for publishing messages with amqp application properties
- publish performance test results for message publishing
- include aiokafka and apache kafka in message publishing performance tests
- fix potential buffer overflow issues when decoding message publishing confirmations
- use cython 3.0.0b2 to build rbfly binary extensions
- rename `PublisherBatch` class as `PublisherBatchFast` class
- rename `PublisherBatchMem` class as `PublisherBatchLimit` class

2023-05-12, ver. 0.6.2

- fix parsing of virtual host in rabbitmq streams uri, i.e. `/vhost` -> `vhost` but `/` remains as `/`

2023-03-18, ver. 0.6.1

- fix message id value type; it is 64-bit, not 32-bit value

2023-02-04, ver. 0.6.0

- fix various buffer overflow issues
- split batch of messages, and send multiple batches, when the batch is too big to fit into rabbitmq streams protocol frame
- increase initial credit value to 128; this improves performance of reading messages with rabbitmq 3.11.8; the possible memory footprint of 400 MB to read messages still seems to be acceptable
- adapt to rabbitmq 3.11.8 changes related to the handling of stream subscription credit

12.3 Year 2022

2022-12-22, ver. 0.5.6

- fix processing of credit value of rabbitmq stream subscription, when messages were published in batches

2022-12-19, ver. 0.5.5

- improve maintenance of rabbitmq stream's subscription credit

2022-11-23, ver. 0.5.4

- fix authentication with rabbitmq streams broker (send password if specified, not username)

2022-11-11, ver. 0.5.3

- use recursive definition for container amqp types, i.e. sequence can contain another sequence or a dictionary
- documentation improvements

2022-11-01, ver. 0.5.2

- fix encoding of binary data in containers, i.e. list of elements having bytes type

2022-10-16, ver. 0.5.1

- fix deadlock of rabbitmq streams protocol publish method when no messages are sent

2022-10-09, ver. 0.5.0

- implement rabbitmq streams batching publisher with memory protection and concurrently working from multiple asynchronous coroutines
- send heartbeat if there is no communication from rabbitmq streams broker and restart connection if no response

2022-09-12, ver. 0.4.2

- allow sending messages via a streams publisher from multiple coroutines
- improve rabbitmq streams connection decorator type annotations

2022-08-16, ver. 0.4.1

- minor fixes post 0.4.0 release

2022-08-16, ver. 0.4.0

- add support for encoding and decoding of timestamp and UUID values in amqp 1.0 codec
- add support for decoding of message annotations and application properties of amqp message
- fix amqp decoder when dealing with unsigned char values (i.e. size of a byte string)
- fix storing of rabbitmq streams timestamp in message context object

2022-05-23, ver. 0.3.0

- api change: do not store stream offset value in stream subscription method to give more control over the action to a programmer
- implement rabbitmq streams client method to store stream offset value
- implement function to get message context for a received stream message

2022-05-13, ver. 0.2.0

- change publisher reference name scheme to <hostname>/<pid>
- allow to set publisher reference name when creating a stream publisher
- improve handling of rabbitmq streams disconnections
- increase sleep time when retrying stream subscription or rabbitmq streams broker reconnection (current sleep time is too aggressive with simple broker restart)

2022-04-13, ver. 0.1.1

- fix handling of multiple disconnection requests, i.e. when multiple coroutines share a client
- properly propagate asynchronous generators via the connection decorator

2022-04-06, ver. 0.1.0

- improvements to decoding of amqp messages
- fix compilation issues on macos and freebsd operating systems

2022-03-25, ver. 0.0.4

- add support for value of type list in amqp messages

2022-03-24, ver. 0.0.3

- add support for values of type boolean, integer, float, and dictionaries in amqp messages

2022-01-24, ver. 0.0.2

- fix encoding of messages

2022-01-16, ver. 0.0.1

- initial release
- genindex

Index

A

AMQPAppProperties (in module *rbfly.types*), 20
AMQPBody (in module *rbfly.types*), 20
AMQPScalar (in module *rbfly.types*), 20

B

batch() (*rbfly.streams.PublisherBatchFast* method), 18
batch() (*rbfly.streams.PublisherBatchLimit* method), 18

C

connection() (in module *rbfly.streams*), 15
create_stream() (*rbfly.streams.StreamsClient* method), 15

D

delete_stream() (*rbfly.streams.StreamsClient* method), 15

F

FIRST (*rbfly.streams.Offset* attribute), 19
flush() (*rbfly.streams.PublisherBatchFast* method), 19
flush() (*rbfly.streams.PublisherBatchLimit* method), 18

G

get_message_ctx() (in module *rbfly.streams*), 17

L

LAST (*rbfly.streams.Offset* attribute), 19

M

message_id (*rbfly.streams.Publisher* attribute), 17
message_id (*rbfly.streams.PublisherBatchFast* attribute), 18
message_id (*rbfly.streams.PublisherBatchLimit* attribute), 18
MessageCtx (class in *rbfly.streams*), 19
module
 rbfly.streams.offset, 8

N

name (*rbfly.streams.Publisher* attribute), 17
name (*rbfly.streams.PublisherBatchFast* attribute), 18
name (*rbfly.streams.PublisherBatchLimit* attribute), 18
NEXT (*rbfly.streams.Offset* attribute), 19

O

Offset (class in *rbfly.streams*), 19
offset() (*rbfly.streams.Offset* static method), 19

P

Publisher (class in *rbfly.streams*), 17
publisher() (*rbfly.streams.StreamsClient* method), 15
PublisherBatch (class in *rbfly.streams*), 20
PublisherBatchFast (class in *rbfly.streams*), 18
PublisherBatchLimit (class in *rbfly.streams*), 17
PublisherBatchMem (class in *rbfly.streams*), 20

R

rbfly.streams.offset
 module, 8
reference() (*rbfly.streams.Offset* static method), 19

S

send() (*rbfly.streams.Publisher* method), 17
stream (*rbfly.streams.Publisher* attribute), 17
stream (*rbfly.streams.PublisherBatchFast* attribute), 18
stream (*rbfly.streams.PublisherBatchLimit* attribute), 18
stream_message_ctx() (in module *rbfly.streams*), 16
streams_client() (in module *rbfly.streams*), 15
StreamsClient (class in *rbfly.streams*), 15
subscribe() (*rbfly.streams.StreamsClient* method), 16
Symbol (class in *rbfly.types*), 20

T

timestamp() (*rbfly.streams.Offset* static method), 19

W

write_offset() (*rbfly.streams.StreamsClient* method), 16